

RET1000 Smart Room Thermostat

Features



RET1000 Smart Room Thermostats combine sleek modern design with high performing energy saving control. The well-proportioned dial and clear temperature scale makes setting easy, including an easy to set upper and lower temperature limiting feature. All RET1000 thermostats include stylish backlit LED icons providing clear indication of power and output status. As well as standard on/off control the user can select to benefit from Danfoss chrono-proportional control. Normally set at installation although easy to change via a DIP switch this micro-processor based control system will deliver increased comfort and improved economy.

When chrono-proportional mode is set, the thermostat introduces a fixed cycle rate on the system and then determines the duration of the On and Off periods within each cycle in proportion to load. The control algorithm used to determine the on/off periods uses a proportional + integral (PI) routine to eliminate offset normally associated with on/off or simple proportional control.

Chrono-proportional control significantly improves comfort and generally improves boiler efficiency by optimising water temperature.

- Selectable Chrono Proportional or On/Off control
- User Set Upper and Lower Temperature Limits
- Output On Indication
- Power Indication

Installer Settings

On/Off Control

Switch	Setting	Function
1		On/Off
2		Not Active
3		Not Active
4		Not Active

Chrono-Proportional Control

Switch	Setting	Function
1		Chrono
2		3 cycles per hour
3		3 cycles per hour
4		Not Active
or 1		Chrono
2		6 cycles per hour
3		6 cycles per hour
4		Not Active
or 1		Chrono
2		12 cycles per hour
3		12 cycles per hour
4		Not Active

Datasheet

RET1000 Smart Room Thermostat

Specifications and Ordering Information

Thermostat Features	RET1000MS	RET1000M	RET1000B
Ordering codes	087N645200	087N645000	087N645100
Product Line	03		
Type	Dial Thermostat		
Power Supply	230Vac +/-15%, 50/60Hz		2.5 – 3VDC (2xAA batteries)
Output	230Vac	Volt free	
Setting temperature range	5-30 °C		
Operating temperature range	0-45 °C		
Switch rating	3A at 230Vac		
Switch type	SPDT type 1B		
Battery lifetime	N/A		Min. 2 years
IP Rating	IP20		
On/Off Control	Yes		
Chrono-proportional control	Yes		
Dimensions (mm)	H84 x W84 x D37		

Product Conversion Table


New Part	Can Replace
RET1000MS	RET230, RET230L
RET1000M	RET230VF, RET230VF2
RET1000B	New

ErP Class



ERP Class		
The products represented within this document are classified according to, and allow completion of, the Energy Related Product (ErP) Directive System Package fiche and the ErP system data label. ErP Labelling obligation is applicable from 26th September 2015.		
ErP Class	Product Function and ErP Description	Additional efficiency gain
IV	TPI Room Thermostat, for use with on/off output heaters An electronic room thermostat that controls both thermostat cycle rate and in-cycle on/off ratio of the heater proportional to room temperature. TPI control strategy reduces mean water temperature, improves room temperature control accuracy and enhances system efficiency.	2%

Wiring Details



Danfoss Ltd.

Ampthill Road
Bedford MK42 9ER
Tel: 01234 364621
Fax: 01234 219705
Email: ukheating@danfoss.com
Website: www.heating.danfoss.co.uk

Danfoss can accept no responsibility for possible errors in catalogues, brochures, and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without consequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.